SHARE

Skid-Steer Loaders / S650 Skid-Steer Loader

Specifications & Options

Standard	Optional	N/A Not Applicable		Units

Bobcat S650

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	74 hp
Turbocharged Engine	✓

Performance

Rated Operating Capacity (ISO)	2,690 lb
Tipping Load	5380 lb
Operating Weight	8061 lb
Travel Speed	7.1 mph
Travel Speed (2-speed option)	12.3 mph

Capacities

Fuel Tank	23.9 gal
-----------	----------

Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	23 gal/min
Auxiliary High Flow	30.5 gal/min

Dimension

Length	136.8 in
Length without Attachment	108.4 in
Length with Standard Bucket	136.8 in
Width	72.1 in
Width (with bucket)	74 in
Height	81.3 in
Height with Operator Cab	81.3 in
Height to Bucket Hinge Pin	124 in
Reach @ Maximum Height	31.5 in
Turning Radius	82.9 in
Wheelbase	45.3 in

Features

Joystick Control	✓
Air Conditioning	✓
Adjustable Seat	•
Backup Alarm	•
BICS System (Interlock)	•
Cab Enclosure	▽
Sound Option	✓
Cab Heater	✓
Operating Lights	•
Parking Brake	•
Radio	✓
Rear Window	•
Top Window	=
Lift-Arm Support	•
Seat Belt	•
Suspension Seat	•
Two Speed Travel	✓
Deluxe Instrumentation	✓
Engine Shutdown	•
Hydraulic Bucket Positioning	▼
High Flow Option	✓
Auxiliary Hydraulics	•
Spark Arrestor Muffler	•
Bob-Tach Attachment System	•
Power Bob-Tach	✓
ACS (Switchable Controls)	✓
Ride Control	▽
Rear Hydraulics	✓
Horn	•

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.