SHARE

Skid-Steer Loaders / S570 Skid-Steer Loader

Specifications & Options

Standard	Optional	N/A Not Applicable	Units

Bobcat S570

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	61 hp
Turbocharged Engine	▽

Performance

Rated Operating Capacity (ISO)	1,950 lb
Tipping Load	3900 lb
Operating Weight	6480 lb
Travel Speed	7.4 mph
Travel Speed (2-speed option)	11 mph

Capacities

Fuel Tank	24.8 gal
-----------	----------

Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	17.1 gal/min
Auxiliary High Flow	26.7 gal/min

Dimension

Length	133 in
Length without Attachment	104.6 in
Length with Standard Bucket	133 in
Width	64.7 in
Width (with bucket)	68 in
Height	77.8 in
Height with Operator Cab	77.8 in
Height to Bucket Hinge Pin	119 in
Reach @ Maximum Height	32.6 in
Turning Radius	79.7 in
Wheelbase	42.6 in

Features

Joystick Control	✓
Air Conditioning	✓
Adjustable Seat	•
Backup Alarm	•
BICS System (Interlock)	•
Cab Enclosure	▽
Sound Option	✓
Cab Heater	✓
Operating Lights	•
Parking Brake	•
Radio	✓
Rear Window	•
Top Window	=
Lift-Arm Support	•
Seat Belt	•
Suspension Seat	•
Two Speed Travel	✓
Deluxe Instrumentation	✓
Engine Shutdown	•
Hydraulic Bucket Positioning	▼
High Flow Option	✓
Auxiliary Hydraulics	•
Spark Arrestor Muffler	•
Bob-Tach Attachment System	•
Power Bob-Tach	✓
ACS (Switchable Controls)	✓
Ride Control	▽
Rear Hydraulics	✓
Horn	•

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.