RELAWNY

SCABBLING

11 HEAD CONCRETE FLOOR SCABBLER



FEATURES & BENEFITS

- 11 replaceable carbide tipped scabbling heads for fast production and long service life
- 4,000 light blows per minute for fast production without damaging the underlying substrate
- Trelawny Vibro-Lo[™] vibration reduction system for protection of operators
- Optional Trelawny TVS[®] vacuum shroud system for protection of operators and surrounding environment

MHS11

DEVELOPED IN CONJUNCTION WITH THE 'CITB - CONSTRUCTION INDUSTRY TRAINING BOARD'.

The MHS11 introduces a new concept in pneumatic floor scabblers. Using smaller heads with a 70% increase in BPM (Blows Per Minute) and a 30% reduction in air consumption, the MHS11 maximises productivity, efficiency, value and ergonomics, without compromise.

Its is the perfect machine for fast removal of laitance, level reduction and profiling for new concrete and thick screeds and sealants.

Production rates in excess 30 m² per hour.



Low vibration



Dust control options available See page 72 for our full range of vacuums

APPLICATIONS


- Removal of laitance, roughening, and reduction of levels
- Aggressive keying without damaging the substrate
- Removal of coatings
- Fast removal of hazardous coatings and contaminated materials with TVS[®] shroud system



CONCRETE SCABBLING



FITTED WITH DUST SHROUD



LAITANCE REMOVAL

IRELAWNY

SCABBLING

11 HEAD CONCRETE FLOOR SCABBLER

MHS11

KEY CONSUMABLES & ACCESSORIES

Image	Part Number	Description	Image		Part Number	Description	
	612.0125	One piece piston, tungsten carbide tipped, bush hammer head To suit models 159.6050 and 159.6051			437.0120	Vacuum Shroud	
	612.0224	Pin fit piston to fit replaceable head To suit model 159.6000 and 159.6100		\bigcirc	815.5550	Whip Check	
	441.5455	Pin fit Replaceable cutter head, tungsten carbide tipped, bush hammer head To suit model 159.6000			859.1580	%" BSP inline lubricator	
	441.5460	Pin Fit Replaceable cutter head, tungsten carbide tipped, cruciform head To suit model 159.6100			458.1580	Whip Hose & Oiler Assembly Consists of whip hose, whip check and ¾" lubricator	
0	614.5302	Brush seal			715.0752	%" Air Hose Complete with couplings 15m length	

TECHNICAL DATA

Model	Part Number	Weight (kg)	Length (mm)	Height (mm)	Width (mm)	Cutting Width (mm)	Blows per Minute (BPM)	Air Consumption (lps - cfm)	Noise Level (db (A))	Vibration Level (Aeq m/s²)
MHS11 One Piece Bush Piston	159.6050	70	340	1290	285	250	2200 x 11	26 - 55	97	4.96 🙆
MHS11 One Piece Bush Piston c/w Shroud	159.6051	72	340	1290	285	250	2200 x 11	26 - 55	97	4.96 🙆
MHS11 Two Piece Bush Piston	159.6200	70	340	1290	285	250	2200 x 11	26 - 55	97	4.96 🙆
MHS11 Two Piece Bush Piston c/w Shroud	159.6201	72	340	1290	285	250	2200 x 11	26 - 55	97	4.96 🙆
MHS11 Two Piece Cruciform Piston	159.6210	70	340	1290	285	250	2200 x 11	26 - 55	97	4.96 🙆
MHS11 Two Piece Cruciform Piston c/w Shroud	159.6211	72	340	1290	285	250	2200 x 11	26 - 55	97	4.96 🚱