

HANDHELD PNEUMATICS

When you get a Chicago Pneumatic tool in your hands, everything just feels right. It's balanced for improved control. The grips fit your hands. It's solid and rugged, yet lightweight for jobsite maneuverability.

Turn the tool on and it feels like an extension of your arms, letting you focus on the job and not the tool. The power flows. The toughness is clear. It's performance in the palm of your hand. It's our handheld pneumatic tool.

BREAKERS



Applications

- Used in demolition, construction, renovation, road construction, bridge work and street repairs

Features

- Robust and proven design
- Built-in vibration reduction (SVR model)
- Alloy steel forgings for excellent durability
- Easy and comfortable to operate
- Easy access to daily service points
- Easy to transport
- All models equipped with mufflers for noise reduction

PNEUMATIC BREAKERS	CP 0112 S	CP 1210 S	CP 1210 S	CP 1210 SVR	CP 1210 SVR	CP 1260 S	CP 1260 SVR	CP 0117 S	CP 1290 S	CP 1290 SVR
Weight kg	14.5	22	22.5	24.5	25	31	34	36	39	43.5
Length mm	535	540	585	600	650	680	735	740	730	785
Air Consumption l/s	23	26.5	26.5	26.5	26.5	34.5	34.5	35	43	43
Blows Per Minute bpm	1,620	1,400	1,400	1,400	1,400	1,300	1,300	1,080	1,100	1,100
Vibration Level 3 Axes (ISO 20643) m/s ²	16.3	14.6	14.6	5.3	5.3	20.7	6.5	11.9	18.4	6.2
Sound Power Level Guaranteed (12000/14/EC) dB(A)	105	105	105	105	105	110	110	108	111	111
Sound Pressure Level (ISO 11203) dB(A)	93	92	92	92	92	97	97	95	98	98
Retainer Type	Latch	Latch	Latch	Latch	Latch	Latch	Latch	Latch	Latch	Latch
Air Inlet	3/4" NPTF	3/4" NPTF	3/4" NPTF	3/4" NPTF	3/4" NPTF	3/4" NPTF	3/4" NPTF	3/4" NPTF	3/4" NPTF	3/4" NPTF
Part Number (ISO Std Shank) Chuck: 25 x 108 mm	8900 0030 25	8900 0030 04	-	8900 0030 06	-	-	-	-	-	-
Part Number Chuck: 28 x 160 mm	-	-	8900 0030 07	-	8900 0030 08	8900 0030 31	8900 0030 33	T022093	8900 0030 40	8900 0030 42
Part Number Chuck: 32 x 160 mm	-	-	8900 0030 09	-	8900 0030 10	8900 0030 30	8900 0030 32	T022092	8900 0030 39	8900 0030 41

SPIKE DRIVERS



Applications

- Used for driving spikes in railroad, construction and plant maintenance applications

Features

- Robust, powerful design
- Heavy-duty front head springs for reduced reaction back to operator
- Alloy steel forgings for excellent durability
- Built-in lubricator
- Easy access to daily service points
- Lightweight and easy to transport
- All models equipped with mufflers for noise reduction

PNEUMATIC SPIKE DRIVERS	CP 1260 S SPDR	CP 1290 S SPDR
Weight kg	29.5	38
Length mm	625	660
Air Consumption l/s	34.5	43
Blows Per Minute bpm	1,300	1,110
Vibration Level 3 Axes (ISO 20643) m/s ²	20.7	18.4
Sound Power Level Guaranteed (2000/14/EC) dB(A)	110	111
Sound Pressure Level (ISO 11203) dB(A)	97	98
Air Inlet	3/4" NPTF	3/4" NPTF
Max Head Diameter mm	44	44
Part Number	8900 0030 34	8900 0030 43